

Giving Shape to Ideas





bizhub C258

Ideal for growing businesses, the bizhub C258 is a powerful, affordable color MFP with superior Simitri HD image quality and fast 25 ppm print/copy output. Optional dual scanning at up to 160 opm brings information into your workflow faster— and enhanced touch-screen simplicity never slows you down.

System Overview	
System memory	4 GB (when UK-211 is installed)
System hard disk	250 GB Standard
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Document feeder	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163 gsm
(optional)	Reversing automatic document feeder or dual scan document feeder available
Printable paper size	Scanning/Copying: up to 11" x 17" Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray LU-302 (optional)	3,000 sheets / 8.5" x 11" / 52-256 gsm
Large capacity tray PC-410 (optional)	2,500 sheets / 8.5" x 11" / 52-256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, staple, sort, punch, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 50 sheets or 48 sheets + 2 cover sheet (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 80,000 pages/month ¹
Toner lifetime	Black: 28,000 pages / CMY: 26,000 pages
Imaging unit lifetime	Black: 120,000 pages / 600,000 pages (Drum / Developer) CMY: 55,000 pages / 600,000 pages (Drum / Developer)
Power consumption	120 V / 60 Hz, less than 1.5 kW (system)
System dimensions	24.2" x 27" x 31" (W x D x H)
System weight	Approx. 187.39 lb

•	ni,	· · C	'n	_ifi	00	tior	20

Copying process	Electrostatic laser copy, tandem, indirect		
Toner system	Simitri® HD Polymerized Toner		
Print speed (8.5" x 11")	B&W / Color: up to 25 ppm (Portrait)		
Print speed (11" x 17")	B&W / Color: up to 15 ppm (Portrait)		
Autoduplex speed (8.5" x 11")	B&W / Color: up to 25 ppm (Portrait)		
1st copy out time	B&W: 6.1 sec. / Color: 7.5 sec.		
Warm-up time	Approx. 20 sec. ²		
Copy resolution	600 x 600 dpi		
Gradations	256 gradations		
Multi-copy	1-9,999		
Original format	Up to 11" x 17"		
Magnification	25-400% in 0.1% steps, auto zooming		
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1		

Printer Specifications

i ilittoi opooliioationo			
Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi		
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS		
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.6 or later Linux / Citrix		
Printer fonts	80 PCL Latin, 137 PostScript 3		
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print		

Printer Specifications (Optional)

Print controller	Embedded Fiery IC-416
Memory/HDD	2 GB / 500 GB
PDL	PostScript 3 (ver. 3019)
	PCL 6/5c
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 / 10
	Macintosh OS X 10.11 or later

Scanner Specifications

Scan speed	B&W / Color: up to 160 ipm with optional DF-704
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

Fax Specifications

Fax	Super G3 (optional)
Transmission	Analog, Internet fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/FTP/SMB, up to 400 job programs

User Box Specifications

Storable documents	Max.: 3,000 documents or 10,000 pages		
Type of user boxes	Public		
	Personal (with password or authentication) Group (with authentication)		
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation		
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax), copy box-to-box		

System Features

Security	ISO 15408 EAL
	IEEE 2600.1
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	FIPS 140-2
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt,
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + Email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

¹ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.
1 This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs
2 Warm-up time may vary depending on the operating environment and usage
3 Supports x64 only

Components and Options

Components and Option	S
AU-102 Biometric	Finger vein scanner
authentication AU-204H Magnetic	Requires WT-506 Working Table
stripe card reader	Tiequiles W1-500 Working Table
AU-205H Universal	Various ID card technologies
ID card reader AU-211 CA/PIV	Requires WT-506 Working Table
solution	Tioquiles W1 500 Working lable
DF-629	Reversing automatic document feeder, capacity 100 originals
Document feeder DF-704	Dual scan automatic document feeder, capacity 100 originals
Document feeder	dual scall automatic document recuel, capacity 100 originals
DK-510 Copier desk	Provides storage space for print media and other materials
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board FS-533 Staple finisher	Super G3 fax, digital fax functionality, lines 3 & 4 support 50-sheet stapling, 500 sheets max. output
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	3,300 sheets max. output
HD-524 Hard disk IC-416 Fiery	Hard disk mirroring, 250 GB Embedded image controller for graphics-intensive applications
image controller	Emboduod imago controller for graphics intensive applications
JS-506 Job separator	Separation for fax output, etc.
KH-102 Keyboard holder	To place USB keyboard
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	Du the dead there (are a
LK-104 v3 Voice guidance	Provides voice guidance functions
LK-105 v4	Searchable PDF
OCR text recognition	
LK-106 Barcode fonts	Supports native barcode printing
LK-107	Supports native Unicode printing
Unicode fonts	
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111 ThinPrint® Client	Print data compression for reduced network impact
LU-302	8.5" x 11", 3,000 sheets / 52-256 gsm
Large capacity unit	
MK-730 Mount kit MK-735 Mount kit	Banner paper guide
MK-742 Mount kit	Installation kit for ID card reader Installation kit for FK-515 fax board
OC-511 Original cover	Cover instead of auto document feeder
PC-110	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm
Universal tray (x1) PC-210	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm
Universal tray (x2)	5.5 x 6.5 to 11 x 17 , 2 x 500 sheets, 52-250 ysin
PC-410	8.5" x 11", 2,500 sheets, 52-256 gsm
Large capacity tray	2/3-hole punching, autoswitching
PK-519 Punch kit for FS-533	2/3-note puriching, autoswitching
PK-520 Punch kit for FS-534	2/3-hole punching, autoswitching
RU-513 Relay unit	Required for the FS-534
SC-508 Security kit	Copy Guard function (2x required when DF-704 is installed)
SK-602 Staple kit	Added stapling functionality kit
SP-501 Stamp unit	Added fax stamp capability kit
UK-211	2 GB memory expansion, required for most i-Options, registered overlay, and concurrent use of web browser and certain other
	functions, including stamp print, watermark, date/time print, header/
III. 040 III. 1	footer, image overlay and management number
UK-212 Wireless LAN VI-508 Interface kit	Wireless LAN to network connector
vi-508 interface kit for IC-416	Fiery controller interface card
WT-506 Working table	Authentication device placement